

**Saber S.r.l.**

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy
Tel: +39 0375 782083 - Fax: +39 0375 780055
info@sabercolor.com - bernini@pec.sabercolor.com
Partita IVA e Codice fiscale 00289400202
Capitale Sociale € 30.000 - REA: MN 127583

SCHEDA TECNICA ISOLMUR**Cod. 035.2000 – Rev. 11/2023**

CLASSIFICATION	Smooth pigmented filler water-based paint based on quartz flours. Easy to apply and good expansion.											
KIND OF USE	For the reinforcement and protection of plaster, exposed brick, gypsum, cement, wood, sandstone and limestone which will be finished with finishes such as coatings and/or paints. EXCELLENT FILLING. It enhances the covering and unifying power of the finishes, ensuring greater fullness.											
CHEMICAL COMPOSITION	Acrylic in aqueous emulsion.											
TECHNICAL DATA	Appearance: liquid Specific weight: 1.320+-0.050 kg/L Color: White Viscosity of supply: 6000 +- 2000 cps Brilliance: matt											
APPLICATION SYSTEM	Brush – Roller - Spray.											
DILUTION	10-20% by weight.											
MEDIUM OUTPUT	7-8 mq/L.											
COV READY TO USE MIXTURE	CLASSIFICATION ACCORDING TO DIRECTIVE 2004/42/EC – Legislative decree 161/06: Cat. h-BA MINERAL SUPPORT PAINTS FOR EXTERNAL WALLS EU limits 2010 40 gr/lit. COV OF PRODUCT 5 gr/lit											
DRYING	<table><tr><th colspan="3"><u>AIR DRYING at 20 ° C - 60% humidity</u></th></tr><tr><td>Out of touch</td><td>in the depth</td><td>time to paint over</td></tr><tr><td>30-60 mins</td><td>3 hrs</td><td>6-8 hrs</td></tr></table>			<u>AIR DRYING at 20 ° C - 60% humidity</u>			Out of touch	in the depth	time to paint over	30-60 mins	3 hrs	6-8 hrs
<u>AIR DRYING at 20 ° C - 60% humidity</u>												
Out of touch	in the depth	time to paint over										
30-60 mins	3 hrs	6-8 hrs										
MIN. TEMPERATURE OF APPLICATION	+ 5° C											
PREPARATION OF THE SURFACE	FOR NEW SURFACE: apply a coat of ISOLMUR (the dilution depends on the absorption of the Surface). FOR OLD SURFACE: Clean and remove any loose parts. Proceed with ISOLMUR and, once dry, with the subsequent finishing. In the case of colored finishes, ISOLMUR can be colored with up to a maximum of 5% of pastes to avoid altering the characteristics of the product. Colorable on request.											
CLEANING OF EQUIPMENT AND TOOLS	With water immediately after use.											
NOTE	Available in 14 L buckets. For the possible feasibility of colors on request, contact our technical office											
WAREHOUSE STABILITY	1 year in original sealed containers.											
STORAGE	The product must be stored in its original intact packaging in an environment that must be protected from frost and excessive heat and therefore with a temperature not lower than +5 °C and not higher than +25 °C. Information relating to labelling and handling is contained in the relevant safety data sheet. Liquid or solid waste and empty containers must be disposed of according to local regulations. FEARS FROST.											

The information, data and suggestions contained in this technical sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case, they cannot imply a guarantee on our part, as the conditions of use are outside our strict control, therefore do not exempt the customer from the burden and responsibility of verifying the suitability of the product for the specific intended use.