

**Saber S.r.l.**

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy  
 Tel: +39 0375 782083 - Fax: +39 0375 780055  
 info@sabercolor.com - [bernini@pec.sabercolor.com](mailto:bernini@pec.sabercolor.com)  
 Partita IVA e Codice fiscale 00289400202  
 Capitale Sociale € 30.000 - REA: MN 127583

## TECHNICAL DATA SHEET ALICANTE

**Cod. 186. – Rev. 05/2022**

CLASSIFICATION	Water-based smooth pearlescent decorative finish for interiors with great coverage and excellent brushability.						
KIND OF USE	The product is indicated as a finishing layer for the protection and decoration of inner surfaces. Alicante has an excellent pearlescent metallic finish with shiny-satin contrast and a very fine decorative effect.						
CHEMICAL COMPOSITION	acrylic copolymer modified in water emulsion						
TECHNICAL DATA	Appearance: paste Specific weight: 1,100+-0.020 kg/L Color: BASE: Gold-Bronze-Copper-Light Gold-Pearl Viscosity of supply: 7000 +- 1500 cps Brilliance: Pearlescent-shiny						
APPLICATION SYSTEM	Brush – Spalter.						
DILUTION	Ready-to-use product. if necessary 3-5% with water, maximum.						
AVERAGE OUTPUT	9-10 mq/L with one coat.						
COV READY TO USE MIXTURE	CLASSIFICATION ACCORDING TO DIRECTIVE 2004/42/EC – Legislative decree 161/06: Cat. A/I-BA DECORATIVE EFFECTS PAINT EU limits 2010 200 gr/lt. COV OF PRODUCT 30 gr/lt						
DRYING	<u>AIR DRYING at 20 ° C - 60% humidity</u> <table><tr><td>Out of touch</td><td>in the depth</td><td>time to paint over</td></tr><tr><td>30-60 minutes</td><td>2-3 hours</td><td>4-5 hours</td></tr></table>	Out of touch	in the depth	time to paint over	30-60 minutes	2-3 hours	4-5 hours
Out of touch	in the depth	time to paint over					
30-60 minutes	2-3 hours	4-5 hours					
MIN. TEMPERATURE OF APPLICATION	+ 5° C						
PREPARATION OF THE SURFACE	FOR NEW stabilized surfaces, brush the surface thoroughly and apply a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of white levelling DAS. FOR OLD SURFACES, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with filler. Then proceed with the preparation as for new surfaces.						
APPLICATION	On a perfectly prepared surface apply a coat of ALICANTE with specific spalter in short and crossed brushstrokes, go over with clean spalter to evenly distribute excess material. To obtain a shinier effect, with more pearlescence, on dry surface, apply a second coat of ALICANTE following the same technique as first.						
CLEANING EQUIPMENT AND TOOLS	With water immediately after use.						
NOTE	Available in buckets of 1 - 4 – 14 litres.						
STORAGE	The product must be stored in its original intact packaging in an environment that must be protected from frost and excessive heat and therefore with a temperature not lower than +5°C and not higher than +35°C. The information relating to labelling and handling are contained in the relative safety data sheet. Liquid or solid residues and empty containers must be disposed of according to local regulations. PROTECT FROM FROST.						

The information, data and suggestions contained in this technical data sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case, they cannot imply a guarantee on our part, as the conditions of use are outside our strict control, therefore they do not exempt the customer from the burden and responsibility of verifying the suitability of the product for the specific use it intends.