

**Saber S.r.l.**

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy  
 Tel: +39 0375 782083 - Fax: +39 0375 780055  
 info@sabercolor.com - [bernini@pec.sabercolor.com](mailto:bernini@pec.sabercolor.com)  
 Partita IVA e Codice fiscale 00289400202  
 Capitale Sociale € 30.000 - REA: MN 127583

**TECHNICAL DATA SHEET AMALFI**

**Cod. 187.000S – Rev. 06/2022**

<b>CLASSIFICATION</b>	Materic decorative finish.						
<b>KIND OF USE</b>	The product is indicated for inner decoration where a soft materic effect is desired given by the alternation of glossy-matt nuances with a slight pearlescence.						
<b>CHEMICAL COMPOSITION</b>	acrylic copolymer modified in water emulsion						
<b>TECHNICAL DATA</b>	<p>Appearance: paste          Specific weight: 1,100±0.020 kg/L          Color: BASE: Gold-Bronze-Copper-Light Gold-Pearl          Viscosity of supply: 7000 ± 1500 cps          Brilliance: Pearlescent-shiny</p>						
<b>APPLICATION SYSTEM</b>	Brush – Spalter.						
<b>DILUTION</b>	maximum 5% with water.						
<b>AVERAGE OUTPUT</b>	8-9 mq/L with one coat.						
<b>COV READY TO USE MIXTURE</b>	CLASSIFICATION ACCORDING TO DIRECTIVE 2004/42/EC – Legislative decree 161/06: Cat. A/I-BA DECORATIVE EFFECTS PAINT EU limits 2010 200 gr/lt. COV OF PRODUCT 25 gr/lt						
<b>DRYING</b>	<p><u>AIR DRYING at 20 ° C - 60% humidity</u></p> <table border="0"> <tr> <td style="padding-right: 20px;">Out of touch</td> <td style="padding-right: 20px;">in the depth</td> <td>time to paint over</td> </tr> <tr> <td style="padding-right: 20px;">1-2 hrs</td> <td style="padding-right: 20px;">3-4 hours</td> <td>4-6 hours</td> </tr> </table>	Out of touch	in the depth	time to paint over	1-2 hrs	3-4 hours	4-6 hours
Out of touch	in the depth	time to paint over					
1-2 hrs	3-4 hours	4-6 hours					
<b>MIN. TEMPERATURE OF APPLICATION</b>	+ 5° C						
<b>PREPARATION OF THE SURFACE</b>	<p>FOR NEW stabilized surfaces, brush the surface thoroughly and apply a coat of acrylic primer SPECIAL FIXATIVE.          On dry surface, apply one or two coats with roller of white levelling DAS.          FOR OLD SURFACES, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with filler.          Then proceed with the preparation as for new surfaces.</p>						
<b>APPLICATION</b>	<p>On a perfectly prepared surface apply a coat of AMALFI with spalter in short and crossed brushstrokes, go over with clean spalter until the desired materic effect is obtained.          To obtain a shinier effect, with more pearlescence, on dry surface, apply a second coat of ALICANTE following the same technique as first.</p>						
<b>CLEANING EQUIPMENT AND TOOLS</b>	<b>With water immediately after use.</b>						
<b>NOTE</b>	Available in buckets of 1 – 2,5 – 14 litres.						
<b>STORAGE</b>	<p>The product must be stored in its original intact packaging in an environment that must be protected from frost and excessive heat and therefore with a temperature not lower than +5°C and not higher than +35°C.          The information relating to labelling and handling are contained in the relative safety data sheet.          Liquid or solid residues and empty containers must be disposed of according to local regulations. PROTECT FROM FROST.</p>						

The information, data and suggestions contained in this technical data sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case, they cannot imply a guarantee on our part, as the conditions of use are outside our strict control, therefore they do not exempt the customer from the burden and responsibility of verifying the suitability of the product for the specific use it intends.