



NAME: ANTIQUUS

CLASSIFICATION: Cellulose based, athermic and aponic decorative paint for interiors, applied with spatula.

KIND OF USE: to protect and decorate inner surfaces. It has an excellent rustic finish, is easy to apply. Suitable for perfectly prepared civil plaster, gypsum and plasterboard

COLOUR: White

CHEMICAL COMPOSITION : titanium dioxide, athermic lamellar charges and synthetic binding.

SPECIFIC WEIGHT :1.280+/-0.030 kg/lt

VISCOSITY OF PRODUCT : thick paste

APPLICATION SYSTEM : plastic spatula or trowel

DILUTION : ready for use. If needed add 2-3% OF WATER MAXIMUM

MEDIUM OUTPUT mq/lt for coat: 1,4-2 mq/lt per coat according to the applied thickness

DRYING: with air at 20°C and 60% relative humidity. Application at +5° C minimum

out of touch	in the depth	time to paint over
2 - 3 hrs	24 hrs	24 hrs

TABLE DIR. 2004/42/CE:

A/1-BA Product= Decorative paint

Limits UE(2010)200 gr/Lt

C.O.V. gr/Lt = 100gr/Lt

Dilution for application= 3% with water

C.O.V. (ready to be used) gr/Lt. = Max 100gr/Lt.

BRILLIANCE : opaque

PREPARATION OF THE SURFACE: If the surface is perfectly stabilized, apply a coat of acrylic primer SPECIAL FIXATIVE and then a coat with roller of uniform white primer DAS.

HOW TO APPLY :

When the surface is dry, apply one coat of Antiquus with a plastic or stainless-steel trowel according to the desired final effect. Once the product is dry, spread the Cera di Pompei waxes with a brush or a sponge, evenly covering the surface, then remove the excess product with a synthetic sponge.

NOTE: Available in lithographed buckets of 14 L, 4 L.

STABILITY IN STOCK : 1 year at +5°/+35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



s.r.l. Via Caduti sul lavoro, 4 46019 Viadana (MN) ITALY - Tel. + 39 0375782083 Fax + 39 0375780055 www.sabercolor.com e-mail : info@sabercolor.com