

Saber S.r.l.

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy
 Tel: +39 0375 782083 - Fax: +39 0375 780055
 info@sabercolor.com - bernini@pec.sabercolor.com
 Partita IVA e Codice fiscale 00289400202
 Capitale Sociale € 30.000 - REA: MN 127583

TECHNICAL DATA SHEET CASTIGLIONI

Cod. 325.FR00 – Rev. 05/2022

CLASSIFICATION	Decorative Finish for interiors with excellent brush application.						
KIND OF USE	The product is specified as a finishing layer for the protection and decoration of interior surfaces made of gypsum, plasterboard or two-layer plastering, conveniently prepared. It has an excellent matte/silky finish given by microparticles, which provides the surface a pleasant marbled effect. It is easy to apply, enhances the effect on smooth surfaces such as gypsum plaster or plasterboard.						
CHEMICAL COMPOSITION	acrylic copolymer modified in water emulsion						
TECHNICAL DATA	Appearance: paste Specific weight: 1,400±0.150 kg/L Color: White with glass microparticles Viscosity of supply: 10600 ± 1000 cps Brilliance: matte/silky						
APPLICATION SYSTEM	Spalter – plastic trowel – brush-						
DILUTION	3-5% of water in one coat, 10% if applied in two coats.						
AVERAGE OUTPUT	10 mq with one coat, 6 mq with two coats.						
COV READY TO USE MIXTURE	CLASSIFICATION ACCORDING TO DIRECTIVE 2004/42/EC – Legislative decree 161/06: Cat. A/I-BA DECORATIVE EFFECTS PAINT EU limits 2010 200 gr/lt. COV OF PRODUCT 30 gr/lt						
DRYING	<u>AIR DRYING at 20 ° C - 60% humidity</u> <table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Out of touch</td> <td style="text-align: center;">in the depth</td> <td style="text-align: center;">time to paint over</td> </tr> <tr> <td style="text-align: center;">30-60 minutes</td> <td style="text-align: center;">2-3 hours</td> <td style="text-align: center;">4-5 hours</td> </tr> </table>	Out of touch	in the depth	time to paint over	30-60 minutes	2-3 hours	4-5 hours
Out of touch	in the depth	time to paint over					
30-60 minutes	2-3 hours	4-5 hours					
MIN. TEMPERATURE OF APPLICATION	+ 5° C						
PREPARATION OF THE SURFACE	On even surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS or of the same color as the finish.						
APPLICATION	On perfectly prepared surface, apply a coat of CASTIGLIONI in desired color with spalter or brush, with short and crossed strokes. To obtain cloudy effect, apply a coat of CASTIGLIONI with spalter in short and crossed strokes and go over with a plastic trowel in circular movements to give the final effect. For a uniform finish, apply the second coat with same technique.						
CLEANING EQUIPMENT AND TOOLS	With water immediately after use.						
NOTE	Available in buckets of 1 - 4 – 14 litres.						
STORAGE	The product must be stored in its original intact packaging in an environment that must be protected from frost and excessive heat and therefore with a temperature not lower than +5°C and not higher than +35°C. The information relating to labelling and handling are contained in the relative safety data sheet. Liquid or solid residues and empty containers must be disposed of according to local regulations. PROTECT FROM FROST.						

The information, data and suggestions contained in this technical data sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case, they cannot imply a guarantee on our part, as the conditions of use are outside our strict control, therefore they do not exempt the customer from the burden and responsibility of verifying the suitability of the product for the specific use it intends.