

NAME: COMETE NEW SERIAL CODE: 325

CLASSIFICATION: Decorative satin covering with crystal light and glitters.

KIND OF USE: The product is indicated as a finishing layer for the protection and decoration of inner surfaces. It has an excellent silky-satin finish with silvery microcrystals. It's easy to apply, suitable for perfectly prepared gypsum, plasterboard and civil plaster surfaces.

COLOUR: White and neutral with silvery microglitters

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.400+/-0.150 Kg/lt

APPLICATION: with brush, roller.

DILUTION: with water at 3-5%

MEDIUM OUTPUT mq/lt per coat: 7-8 mq/two coat

DRYING: with air at $20\,^{\circ}\text{C}$ and humidity $60\,^{\circ}\text{R}$. Application at $+5\,^{\circ}$ C minimum

out of touch in the depth time to paint over 4-5 h 6-8 h

TABLE DIR.2004/42/CE:
A/l-BA Product= Decorative paint
Limits UE(2010)=200 gr/Lt
C.O.V. gr/Lt=130gr/Lt.
Dilution for application= 5% with water

C.O.V. (ready to be used) gr/Lt.= Max 130gr/Lt.

BRILLIANCE: satin

PREPARATION OF THE SURFACE: If the surface is perfectly stabilized, apply a coat of acrylic primer SPECIAL FIXATIVE and then a coat with roller of uniform white primer DAS.

APPLICATION CYCLES: When the surface is perfectly prepared, apply a coat of Comete New with the wanted colour with brush or roller with short and crossed brush strokes. To obtain more concentration of crystals, after 3-4 hours, apply a second coat of Comete new with the same process.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

STABILITY IN STOCK: 1 year at $+5^{\circ}/+35^{\circ}$ C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.

s.r.l. Via Caduti sul lavoro, 4 46019 Viadana (MN) ITALY - Tel. + 39 0375782083 Fax + 39 0375780055 www.sabercolor.com e-mail: info@sabercolor.com