

Saber S.r.l.

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy
 Tel: +39 0375 782083 - Fax: +39 0375 780055
 info@sabercolor.com - bernini@pec.sabercolor.com
 Partita IVA e Codice fiscale 00289400202
 Capitale Sociale € 30.000 - REA: MN 127583

TECHNICAL DATASHEET CRYSTAL

Cod. 336 – Rev. 07/2022

CLASSIFICATION	Water based materic effect decorative finish for interiors with crystals of light and hollow spheres that give anti-condensation properties						
KIND OF USE	Ideal to protect and decorating inner surface. Crystal is an excellent metallic fine effect with light crystals and contrast of shiny/matt relief.						
CHEMICAL COMPOSITION	acrylic copolymer modified in water emulsion.						
TECHNICAL DETAILS	Aspect: Paste Specific Weight: 0,96+-0,020 kg/Lt Color: Pearl Viscosity of supply: 12500 +/- 2000 cps Brilliance: Shiny						
APPLICATION	with brush and spalter.						
DILUTION	Ready to use product. If necessary add maximum 3-5% of water.						
MEDIUM OUTPUT	6-7 mq/L per coats.						
COV READY TO USE	CLASSIFICATION ACCORDING TO DIR. 2004/42/CE - Dlgs 161/06: Cat. A/I-BA DECORATIVE PAINTS Limits EU 2010 200 gr/lt. COV PRODUCT 60 gr/lt						
DRYING	<u>WITH AIR AT 20°C - 60% humidity</u> <table border="0"> <tr> <td>Out of touch</td> <td>in the depth</td> <td>time to paint over</td> </tr> <tr> <td>30-60 mins</td> <td>2-3 hrs</td> <td>4-5 hrs</td> </tr> </table>	Out of touch	in the depth	time to paint over	30-60 mins	2-3 hrs	4-5 hrs
Out of touch	in the depth	time to paint over					
30-60 mins	2-3 hrs	4-5 hrs					
MIN. TEMPERATURE OF APPLICATION	+ 5° C						
PREPARATION OF SURFACE	On new surface, brush thoroughly the surface and apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, to level apply a coat of white primer DAS. On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.						
APPLICATION	When the surface is prepared, apply a coat of CRYSTAL with spalter with short and crossed brush strokes and return with spalter without paint to aggregate materic components to obtain the final effect.						
CLEANING EQUIPMENT AND TOOLS	With water immediately after the use.						
NOTE	Available in packaging of 1L – 4L – 14L.						
STORAGE	The product must be kept in its original intact packaging in an environment which must be protected from freezing and excessive heat and therefore at a temperature not lower than +5 °C and not higher than +35 °C. The information relating to labeling and handling is contained in the relevant safety data sheet. Liquid or solid residues and empty containers must be disposed of according to local regulations. FEAR THE FROST.						

The information, data and suggestions contained in this technical sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case they cannot imply a guarantee on our part, being the conditions of use outside our strict control, therefore they do not release the customer from the burden and responsibility of verifying the suitability of the product for the specific intended use.