

Saber S.r.l.

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy
 Tel: +39 0375 782083 - Fax: +39 0375 780055
 info@sabercolor.com - bernini@pec.sabercolor.com
 Partita IVA e Codice fiscale 00289400202
 Capitale Sociale € 30.000 - REA: MN 127583

TECHNICAL DATA SHEET LEHAR

Cod. 165. – Rev. 01/2023

CLASSIFICATION	Decorative acrylic stucco with a materic effect for interiors and exteriors. It has excellent covering capacity, leveling and easy to spread.						
KIND OF USE	To protect and decorate inner surfaces. Has a satin/gloss metallic finish of fine decorative effect.						
CHEMICAL COMPOSITION	Pearlescent pigments and lamellar charges in acrylic vehicle.						
TECHNICAL DATA	Appearance: paste Specific weight: 1.030+/-0.050 kg/L Color: Pearl Viscosity of supply: 30000 +/- 3000 cps Brilliance: Shiny – Satin.						
APPLICATION SYSTEM	Short haired roller - Trowel.						
DILUTION	Ready-to-use product.						
AVERAGE OUTPUT	4-5 mq/L a coat.						
COV READY TO USE MIXTURE	CLASSIFICATION ACCORDING TO DIRECTIVE 2004/42/EC – Legislative decree 161/06: Cat. A/I-BA DECORATIVE EFFECTS PAINT EU limits 2010 200 gr/lt. COV OF PRODUCT 100 gr/lt						
DRYING	<u>AIR DRYING at 20 ° C - 60% humidity</u> <table border="0" style="margin-left: 40px;"> <tr> <td style="padding-right: 20px;">Out of touch</td> <td style="padding-right: 20px;">in the depth</td> <td>time to paint over</td> </tr> <tr> <td style="padding-right: 20px;">2-3 hrs</td> <td style="padding-right: 20px;">4-6 hrs</td> <td>8-10 hrs</td> </tr> </table>	Out of touch	in the depth	time to paint over	2-3 hrs	4-6 hrs	8-10 hrs
Out of touch	in the depth	time to paint over					
2-3 hrs	4-6 hrs	8-10 hrs					
MIN. TEMPERATURE OF APPLICATION	+ 5° C						
PREPARATION OF THE SURFACE	On new surfaces made of two-layer plaster, well prepared and levelled off, apply a coat of Acrylic primer SPECIAL FIXATIVE with brush. Once dry a coat of white levelling DAS with short haired roller. For old surfaces, brush thoroughly, to remove all loose or flaking parts, restoring the missing parts with stucco, then proceed like for new surface.						
APPLICATION	When the surface is prepared, apply a coat of Lehar with short haired roller. When the product is dry, apply a second abundant coat of Lehar with inox trowel going over the surface with a special tool or zerbino or brush to obtain the final desired effect. When it starts to dry, go over with a clean trowel to obtain desired brilliance.						
CLEANING EQUIPMENT AND TOOLS	With water immediately after use.						
NOTE	Available in buckets of 1 – 4 - 14 L buckets.						
STORAGE	The product must be stored in its original intact packaging in an environment that must be protected from frost and excessive heat and therefore with a temperature not lower than +5°C and not higher than +35°C. The information relating to labelling and handling are contained in the relative safety data sheet. Liquid or solid residues and empty containers must be disposed of according to local regulations. PROTECT FROM FROST.						

The information, data and suggestions contained in this technical data sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case, they cannot imply a guarantee on our part, as the conditions of use are outside our strict control, therefore they do not exempt the customer from the burden and responsibility of verifying the suitability of the product for the specific use it intends.