

Saber S.r.l.

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy
 Tel: +39 0375 782083 - Fax: +39 0375 780055
 info@sabercolor.com - bernini@pec.sabercolor.com
 Partita IVA e Codice fiscale 00289400202
 Capitale Sociale € 30.000 - REA: MN 127583

TECHNICAL DATASHEET MARECHIARO

Cod. 187.00SF – Rev. 09/2022

CLASSIFICATION	Materic decorative finish.						
KIND OF USE	The product is suitable for interior decoration where you want to obtain smooth or embossed materic finishes with a valuable decorative effect.						
CHEMICAL COMPOSITION	Acrylic copolymer, pearlescent micas and ceramic spheres.						
TECHNICAL DATA	Appearance: liquid Specific weight: 1,600+-0,050 Color: Pearl Viscosity of the product: 9000+-1000 cps Brilliance: Satin Pearlescent.						
APPLICATION SYSTEM	Inox trowel, zerbino, plastic trowel with wave design, wood graining tool etc etc.						
DILUTION	Maximum up to 5 % with water.						
MEDIUM OUTPUT	8-9 mq/L a coat						
C.O.V. (READY TO BE USED)	CLASSIFICATION ACCORDING TO DIRECTIVE 2004/42/CE - Dlgs 161/06: Cat. A/I-BA DECORATIVE EFFECT PAINT Limits EU 2010 200 gr/lt. COV OF PRODUCT gr/lt 40						
DRYING	<u>AIR DRYING at 20 ° C - 60% humidity</u> <table><tr><td>Out of touch</td><td>in the depth</td><td>time to paint over</td></tr><tr><td>1 - 2 hrs</td><td>3 - 4 hrs</td><td>4 - 6 hrs</td></tr></table>	Out of touch	in the depth	time to paint over	1 - 2 hrs	3 - 4 hrs	4 - 6 hrs
Out of touch	in the depth	time to paint over					
1 - 2 hrs	3 - 4 hrs	4 - 6 hrs					
MIN. TEMPERATURE OR APPLICATION	+ 5° C						
BASE PREPARATION	FOR NEW well dried surface, brush thoroughly and apply a coat of acrylic primer SPECIAL FIXATIVE with brush. Later apply one or two coats with a roller of levelling Das in the same color as the finish to completely cover the surface. ON OLD surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with stucco, then proceed like for new surface.						
APPLICATION	On a well-prepared surface apply a coat of MARECHIARO with stainless steel trowel going over the surface with the appropriate tool to obtain the desired effect.						
CLEANING EQUIPMENT AND TOOLS	With water immediately after use.						
NOTE	Available in 1 - 2.5 - 14 litres buckets.						
STORAGE	The product must be kept in its original intact packaging in an environment which must be protected from freezing and excessive heat and therefore at a temperature not lower than +5 °C and not higher than +35 °C. The information relating to labeling and handling is contained in the relevant safety data sheet. Liquid or solid residues and empty containers must be disposed of according to local regulations. FEAR THE FROST.						

The information, data and suggestions contained in this technical sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case they cannot imply a guarantee on our part, being the conditions of use outside our strict control, therefore they do not release the customer from the burden and responsibility of verifying the suitability of the product for the specific intended use.