

**Saber S.r.l.**

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy  
 Tel: +39 0375 782083 - Fax: +39 0375 780055  
 info@sabercolor.com - [bernini@pec.sabercolor.com](mailto:bernini@pec.sabercolor.com)  
 Partita IVA e Codice fiscale 00289400202  
 Capitale Sociale € 30.000 - REA: MN 127583

**TECHNICAL DATA SHEET MARMORINO GONZAGA NEW**

**Cod. 320. – Rev. /2022**

<b>CLASSIFICATION</b>	Mineral based Marmorino, applicable with trowel, for marbled finishing.						
<b>KIND OF USE</b>	For the decoration and protection of inner surfaces with excellent shiny/satin marbled finishing. In order to increase its brilliance and shade, it can be finished with our CERE DI POMPEI or our water-based wax CERA ROYAL.						
<b>CHEMICAL COMPOSITION</b>	Long seasoned slaked lime and marble powders.						
<b>TECHNICAL DATA</b>	Appearance: paste Specific weight: 1,400+/-0.050 kg/L Color: White Viscosity of supply: 50000 +/- 5000 cps Brilliance: Shiny – matte.						
<b>APPLICATION SYSTEM</b>	stainless steel (inox) trowel.						
<b>DILUTION</b>	Ready-to-use product.						
<b>AVERAGE OUTPUT</b>	0,8-1 Kg/mq with two coats.						
<b>COV READY TO USE MIXTURE</b>	CLASSIFICATION ACCORDING TO DIRECTIVE 2004/42/EC – Legislative decree 161/06: Cat. A/I-BA DECORATIVE EFFECTS PAINT EU limits 2010 200 gr/lt. COV OF PRODUCT 20 gr/lt						
<b>DRYING</b>	<u>AIR DRYING at 20 ° C - 60% humidity</u> <table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Out of touch</td> <td style="text-align: center;">in the depth</td> <td style="text-align: right;">time to paint over</td> </tr> <tr> <td style="text-align: center;">2 hrs</td> <td style="text-align: center;">48-72 hrs</td> <td style="text-align: right;">8-10 hrs</td> </tr> </table>	Out of touch	in the depth	time to paint over	2 hrs	48-72 hrs	8-10 hrs
Out of touch	in the depth	time to paint over					
2 hrs	48-72 hrs	8-10 hrs					
<b>MIN. TEMPERATURE OF APPLICATION</b>	+ 5° C						
<b>PREPARATION OF THE SURFACE</b>	On surface made of two-layer plaster, well prepared and levelled off, apply a coat of Acrylic primer SPECIAL FIXATIVE with brush and then a coat of white levelling DAS with roller. For new surfaces in gypsum and plasterboard, go on with a coat of Acrylic primer SPECIAL FIXATIVE and then apply a coat of White levelling DAS with roller.						
<b>APPLICATION</b>	on well-dried base, apply the first coat of MARMORINO GONZAGA NEW with INOX trowel by covering the surface evenly. When the first coat is dry, apply the second coat and then the third wet-on-wet. When it starts to dry, go over with a clean trowel to obtain desired brilliance.						
<b>CLEANING EQUIPMENT AND TOOLS</b>	<b>With water immediately after use.</b>						
<b>NOTE</b>	Available in buckets of 5 – 24 kg buckets.						
<b>STORAGE</b>	The product must be stored in its original intact packaging in an environment that must be protected from frost and excessive heat and therefore with a temperature not lower than +5°C and not higher than +35°C. The information relating to labelling and handling are contained in the relative safety data sheet. Liquid or solid residues and empty containers must be disposed of according to local regulations. PROTECT FROM FROST.						

The information, data and suggestions contained in this technical data sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case, they cannot imply a guarantee on our part, as the conditions of use are outside our strict control, therefore they do not exempt the customer from the burden and responsibility of verifying the suitability of the product for the specific use it intends.