



**NAME: MATERIA**  
**SERIAL CODE: BAS.0002**

CLASSIFICATION: Mineral stucco of lime paste for "materic" finish.

KIND OF USE: The product is indicated as a finishing layer for the protection and decoration of inner surfaces. It lends itself to obtaining finishes of good materic effect. In order to increase its brilliance, contrast and intensity of shade, the product can be waxed with our metallized Cere di Pompeii Waxes, or with our transparent Cera Royal water based wax.

COLOUR: white.

CHEMICAL COMPOSITION: marble powder, mineral binding, quartez sands.

SPECIFIC WEIGHT: 1.600+/-0.050 Kg/lt

VISCOSITY OF PRODUCT: thick paste

APPLICATION SYSTEM: inox trowel.

DILUTION: Ready to use. If needed add maximum 3% of water.

MEDIUM OUTPUT mq/lt for coat: 1,7÷2 kg/m2.

DRYING: with air at 20°C and humidity 60%. Application at +5°C minimum.

out of touch	in the depth	time to paint over
2 hrs	48-72 hrs	8-10 hrs

TABLE DIR.2004/42/CE :

A/1-BA Product= Decorative paint.

Limits UE(2010)= 40 gr/lt

C.O.V. gr/Lt = 200 gr/Lt.

Dilution for application= 0% with water

C.O.V. (ready to be used) gr/Lt.= Max 20gr/Lt.

BRILLIANCE: matt

PREPARATION OF THE SURFACE: For perfectly stabilized civil plaster surfaces, apply a brush coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS.

For perfectly stabilized gypsum or plasterboard substrates, apply a brush coat of acrylic primer Special Fixative and then a roller coat of uniform white primer DAS.

APPLICATION CYCLES : on well-dried base, apply the first coat of MATERIA with INOX trowel by covering the surface evenly. When the first coat is dry, apply the second coat and then the third wet-on-wet.

When it starts to dry, pass the clean trowel over the surface, until you get shiny and opaque areas. Between 48 - 72 hours after application, wax the surface with our Royal Neutral Wax, or with our Cera di Pompei Waxes with a pearlescent effect. Both waxes can be applied with a stainless steel or plastic spatula, or with one synthetic sponge. When the wax is dry, polish with a pad or a woolen cloth.

STABILITY IN STOCK : 1 year at +5°/+35°C in the original sealed containers. Protect from freezing weather.

NOTE: available in buckets Saber of 5 kg - 24 Kg and coloured after evaluating feasibility of the colour. Clean the tools with water.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



