

**Saber S.r.l.**

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy

Tel: +39 0375 782083 - Fax: +39 0375 780055

info@sabercolor.com - bernini@pec.sabercolor.com

Partita IVA e Codice fiscale 00289400202

Capitale Sociale € 30.000 - REA: MN 127583

Technical datsheet Metallika

Cod. 337. – Rev. 09/2022

CLASSIFICATION

Acrylic metallized water finish for interiors with excellent covering and brush application with a velvety effect.

KIND OF USE

The product is indicated as a finishing layer for the protection and decoration of inner surfaces. Metallika presents a shiny/satin/matt effect with an excellent three-dimensional result.

CHEMICAL COMPOSITION

Pearlescent pigments and mattifying fillers dispersed in acrylic vehicle.

TECHNICAL DATA

Appearance: liquid

Specific weight: 1.030+0.050 kg/L

Color: Base: Gold, Bronze, Copper, Light Gold, Pearl.

Brilliance: Shiny – Satin - Matt

APPLICATION SYSTEM

Shorthaired roller – Spalter brush - Plastic trowel.

DILUTION

Ready to use. If needed add maximum 3-5% of water.

MEDIUM OUTPUT

9-10 mq/L with two coats.

COV READY TO USE MIXTURE

CLASSIFICATION ACCORDING TO DIRECTIVE 2004/42/EC – Legislative decree 161/06: Cat. A/I-BA DECORATIVE EFFECTS PAINT EU limits 2010 200 gr/lt. COV OF PRODUCT 100 gr/lt

DRYINGAIR DRYING at 20 ° C - 60% humidity

Out of touch	in the depth	time to paint over
2-3 hrs	4-6 hrs	8-10 hrs

MIN. TEMPERATURE OF APPLICATION

+ 5° C

PREPARATION OF THE SURFACE

FOR NEW stabilized plaster or plasterboard surfaces, carefully dust the surface and apply a brush coat of acrylic fixative, SPECIAL FIXATIVE. On dry surface, apply a coat with roller of levelling filler DAS.

APPLICATION

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster/Stucco. Once the surface is stabilized then proceed like for new surface.

On well-dried base, apply the first coat of METALLIKA with short haired roller, or splatter brush, by covering the surface evenly. When the first coat is dry, apply the second coat with Spalter brush in short and crossed brushstrokes, distributing the paint unevenly. Then go over the surface with Spalter without any paint.

After few minutes from application when the product starts to dry, give the final effect with plastic spatula with small rotating movements.

CLEANING EQUIPMENT AND TOOLS**NOTE**

With water immediately after use.

Available in Packaging of 1 – 4 – 14 Litres.

STORAGE

The product must be stored in its original intact packaging in an environment that must be protected from frost and excessive heat and therefore with a temperature not lower than +5°C and not higher than +35°C. The information relating to labelling and handling are contained in the relative safety data sheet. Liquid or solid residues and empty containers must be disposed of according to local regulations. PROTECT FROM FROST

The information, data and suggestions contained in this technical data sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case, they cannot imply a guarantee on our part, as the conditions of use are outside our strict control, therefore they do not exempt the customer from the burden and responsibility of verifying the suitability of the product for the specific use it intends.