

Saber S.r.l.

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy
 Tel: +39 0375 782083 - Fax: +39 0375 780055
 info@sabercolor.com - bernini@pec.sabercolor.com
 Partita IVA e Codice fiscale 00289400202
 Capitale Sociale € 30.000 - REA: MN 127583

**TECHNICAL DATSHEET STUCCO VENEZIANO
 FONDO Cod. 196 – Rev. 01/2023**

CLASSIFICATION	Acrylic filler for base coat on interior wall surfaces.						
KIND OF USE	The product is used as a base coat for the decoration of interior surfaces with STUCCO VENEZIANO.						
CHEMICAL COMPOSITION	Marble powder and acrylic copolymer.						
TECHNICAL DETAILS	Appearance: Paste Specific Weight: 1,650 +/- 0,070 kg/L Colour: White Viscosity of supply: 25000 +/- 3000 cps Brilliance: Matte						
APPLICATION	Spatula inox – Trowel.						
DILUTION	Ready to use product.						
MEDIUM OUTPUT	7-8 mq/L per coat.						
COV READY TO USE	CLASSIFICATION ACCORDING TO DIR. 2004/42/CE - Dlgs 161/06: Cat. A/I-BA DECORATIVE PAINTS Limits UE 2010 200 gr/lit. COV PRODUCT 130 gr/lit						
DRYING	<u>WITH AIR AT 20 °C – 60% humidity</u> <table border="0"> <tr> <td>Out of touch</td> <td>in the depth</td> <td>time to paint over</td> </tr> <tr> <td>4 – 5 hrs</td> <td>18 – 24 hrs</td> <td>24 –36 hrs</td> </tr> </table>	Out of touch	in the depth	time to paint over	4 – 5 hrs	18 – 24 hrs	24 –36 hrs
Out of touch	in the depth	time to paint over					
4 – 5 hrs	18 – 24 hrs	24 –36 hrs					
MIN. TEMPERATURE OF APPLICATION	+ 5° C						
PREPARATION OF THE SURFACE	On new, well prepared and levelled off surface, apply a coat of Acrylic primer SPECIAL FIXATIVE. On old surfaces, remove all the flaking or spalling parts, dust thoroughly and proceed with putty to restore any surface defects. Apply a coat of Acrylic primer SPECIAL FIXATIVE.						
APPLICATION	On a perfectly dry surface, apply a coat of STUCCO VENEZIANO FONDO with inox trowel by covering, smoothing and levelling the surface evenly.						
CLEANING EQUIPMENT AND TOOLS	With water immediately after the use.						
NOTE	Available in the packaging of 1 – 4 L						
STORAGE	The product must be kept in its original intact packaging in an environment which must be protected from freezing and excessive heat and therefore at a temperature not lower than +5 °C and not higher than +35 °C. Liquid or solid residues and empty containers must be disposed of according to local regulations. FEAR THE FROST.						

The information, data and suggestions contained in this technical sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case, they cannot imply a guarantee on our part, being the conditions of use outside our strict control, therefore they do not release the customer from the burden and responsibility of verifying the suitability of the product for the specific intended use.

Saber S.r.l.

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy
 Tel: +39 0375 782083 - Fax: +39 0375 780055
 info@sabercolor.com - bernini@pec.sabercolor.com
 Partita IVA e Codice fiscale 00289400202
 Capitale Sociale € 30.000 - REA: MN 127583

**TECHNICAL DATSHEET STUCCO VENEZIANO
 LUCIDO Cod. 194 – Rev. 01/2023**

CLASSIFICATION	Self-polishing, water-repellent acrylic putty for interiors.						
KIND OF USE	The product is suitable for the decoration of historic and modern interiors where a very high-level finish with excellent visual impact is desired.						
CHEMICAL COMPOSITION	Acrylic copolymer, titanium dioxide, lamellar fillers.						
TECHNICAL DETAILS	Appearance: Paste Specific Weight: 1,450 +/- 0,050 kg/L Color: White and Neutral Viscosity of supply: 30000 +/- 3000 cps Brilliance: Glossy						
APPLICATION	with plastic spatula – inox trowel.						
DILUTION	Ready to use product.						
MEDIUM OUTPUT	6-7 mq/L two coats.						
COV READY TO USE	CLASSIFICATION ACCORDING TO DIR. 2004/42/CE - Dlgs 161/06: Cat. A/I-BA DECORATIVE PAINTS Limits UE 2010 200 gr/lt. COV PRODUCT 60 gr/lt						
DRYING	<u>WITH AIR AT 20 °C – 60% humidity</u> <table border="0"> <tr> <td>Out of touch</td> <td>in the depth</td> <td>time to paint over</td> </tr> <tr> <td>30 min.- 1 hr</td> <td>8 hrs</td> <td>4 – 6 hrs</td> </tr> </table>	Out of touch	in the depth	time to paint over	30 min.- 1 hr	8 hrs	4 – 6 hrs
Out of touch	in the depth	time to paint over					
30 min.- 1 hr	8 hrs	4 – 6 hrs					
MIN. TEMPERATURE OF APPLICATION	+ 5° C						
PREPARATION OF THE SURFACE	For new surface with civil plaster, gypsum or stabilized plasterboard, apply a brush coat of acrylic primer SPECIAL FIXATIVE. For old surface, brush thoroughly the base, removing dirt and flaking parts and apply some stucco to level off, if necessary, apply then a brush coat of acrylic primer SPECIAL FIXATIVE.						
APPLICATION	When the surface is perfectly prepared, apply a coat of Stucco Veneziano Fondo with a stainless-steel trowel, smoothing the surface carefully and avoiding to leave excess material. When the surface is dry (8 - 10 hours), apply the first coat of Stucco Veneziano Lucido with a stainless-steel trowel, evenly covering the surface. When the surface is dry (4 - 6 hours), apply the second coat with an inox spatula or trowel depending on the type of desired texture. When the product is touch dry but not completely dry, go over the surface with a clean trowel until the desired gloss is obtained. If you want to obtain a mirror-like surface, after polishing with the trowel, wipe the surface with a wool or fur pad, until you get a homogeneous and complete shine.						
CLEANING EQUIPMENTS AND TOOLS	With water immediately after the use.						
NOTE	Available in the packaging of 1 – 4 – 14 L						
STORAGE	The product must be kept in its original intact packaging in an environment which must be protected from freezing and excessive heat and therefore at a temperature not lower than +5 °C and not higher than +35 °C. Liquid or solid residues and empty containers must be disposed of according to local regulations. FEAR THE FROST.						

The information, data and suggestions contained in this technical sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case they cannot imply a guarantee on our part, being the conditions of use outside our strict control, therefore they do not release the customer from the burden and responsibility of verifying the suitability of the product for the specific intended use.