



**NAME: TINTORETTO A SPATOLA NEW**

**SERIAL CODE: 308**

CLASSIFICATION: Putty based on seasoned lime and micronized marble powders. Free of volatile organic compounds (C.O.V.)

KIND OF USE: The product is indicated as a finishing layer for the decoration and protection of inner surfaces of historical or modern structures of particular value. Tintoretto a spatola has a mottled effect finish with light-dark and glossy-satin tones.

COLOUR: White.

FINISH: Matte

CHEMICAL COMPOSITION: Long-seasoned lime putty, marble dust and selected aggregates.

SPECIFIC WEIGHT :1.560+/-0,050 kg/lt

APPLICATION SYSTEM: inox trowel

DILUTION: Ready to use.

MEDIUM OUTPUT mq/lt for coat: 500-700 gr/mq with two coats

DRYING: with air at 20°C and humidity 60%. Application at +20°C  
out of touch                      in the depth                      time to paint over  
2 hrs                                      48-72 hrs                                      6-8 hrs

TABLE DIR.2004/42/CE

A/l-BA Product= Decorative paint

limits UE (2010)=200 gr/Lt

C.O.V. gr/lt=20 gr/Lt.

C.O.V. (ready to be used) gr/Lt.= Max 20 gr/Lt.

PREPARATION OF THE SURFACE: If the surface is perfectly stabilized, apply a coat of acrylic primer SPECIAL FIXATIVE and then a coat with roller of uniform white primer DAS.

OLD SURFACE: brush thoroughly the surface removing dust, dirt and flaking parts and apply some stucco to level off if necessary. Then proceed as new surface.

APPLICATION CYCLES: When the surface is dry, apply a coat of Tintoretto with inox trowel, evenly covering the surface. Then apply one or two coats of this finish with inox trowel depending on the desired effect.

When the surface is cured, but not completely dry, go over with the clean trowel with the little pressure in order to obtain desired shine.

STABILITY IN STOCK: at +5°/+35°C in the original sealed containers. Protect from freezing weather.

NOTE: Available in lithographed buckets of 5 and 24 kg.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



s.r.l. Via Caduti sul lavoro, 4 46019 Viadana (MN) ITALY - Tel. + 39 0375782083 Fax + 39 0375780055 [www.sabercolor.com](http://www.sabercolor.com) e-mail : [info@sabercolor.com](mailto:info@sabercolor.com)