

NAME: TRAVERTINO WHITE

SERIAL CODE: 261

CLASSIFICATION: Lime-based mineral putty for porous effect

finishes.

KIND OF USE: The product is indicated as a finish layer for the protection and decoration of inner surfaces. It has an excellent glossy-satin finish with irregular hollows with a layered effect. In order to increase the brilliance and depth of shade, it is possible to wax the surface with water based wax Cera Royal.

COLOUR: Natural White.

FINISH: Matte

CHEMICAL COMPOSITION: Mineral binder, marble flour, quartz sands.

SPECIFIC WEIGHT :1.690+/-0,050 kg/lt

APPLICATION SYSTEM: inox trowel

DILUTION: Ready to use.

MEDIUM OUTPUT mq/lt for coat: 1-1.3 mq two coats

DRYING: with air at 20°C and humidity 60%. Application at +20°C out of touch in the depth time to paint over 5-6h 2-3 days 20-30 days

TABLE DIR.2004/42/CE

A/1-BA Product= Decorative paint

limits UE (2010) = 200 gr/Lt

C.O.V. gr/lt=20 gr/Lt.

C.O.V. (ready to be used) gr/Lt.= Max 20 gr/Lt.

PREPARATION OF THE SURFACE: If the surface is perfectly stabilized, apply a coat of acrylic primer SPECIAL FIXATIVE and then a coat with roller of uniform white primer DAS.

OLD SURFACE: brush thoroughly the surface removing dust, dirt and flaking parts and apply some stucco to level off if necessary. Then proceed as new surface.

APPLICATION CYCLES: When the surface is dry, apply a coat of Travertino with inox trowel, evenly covering the surface. When the product is dry, apply the second coat of Travertino passing the zerbino trowel over the surface, creating the classic travertino lines. With the product still wet but already in the mineral binder setting phase, pass over the surface an inox trowel, compacting the product and highlighting the hollow texture. while the surface is drying go over again with clean inox trowel to obtain the desired brilliance.

STABILITY IN STOCK: 2 year at $+5^{\circ}/+35^{\circ}$ C in the oiginal sealed containers. Protect from freezing weather.

NOTE: Available in lithographed buckets of 5 and 24 kg.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.

s.r.l. Via Caduti sul lavoro, 4 46019 Viadana (MN) ITALY - Tel. + 39 0375782083 Fax + 39 0375780055 www.sabercolor.com e-mail: info@sabercolor.com