

**Saber S.r.l.**

Via Caduti sul Lavoro, 4 - 46019 Viadana (MN) Italy
Tel: +39 0375 782083 - Fax: +39 0375 780055
info@sabercolor.com - bernini@pec.sabercolor.com
Partita IVA e Codice fiscale 00289400202
Capitale Sociale € 30.000 - REA: MN 127583

TECHNICAL DATASHEET VETUA**Cod. 567.0010 – Rev. 01/2023**

CLASSIFICATION	Water based silky decorative finish with velvety effect.						
KIND OF USE	The product is specified as a finishing layer for the protection and decoration of interior surfaces. Vetua has an excellent pearlescent metallic finish with a velvety effect and fine silky tactility.						
CHEMICAL COMPOSITION	Mica based pearlescent pigments.						
TECHNICAL DETAILS	Aspect: liquid Specific Weight: 1,200+-0,040 kg/Lt Color: Pearl Viscosity of supply: 15000 +/- 2000 cps Brilliance: Gloss						
APPLICATION	Spalter – Stainless steel trowel.						
DILUTION	Ready to use product. If necessary add maximum 3-5% of water.						
MEDIUM OUTPUT	4-6 mq/L with two coats.						
COV READY TO USE	CLASSIFICATION ACCORDING TO DIR. 2004/42/CE - Dlgs 161/06: Cat. A/I-BA DECORATIVE PAINTS Limits EU 2010 200 gr/lit. COV PRODUCT 30 gr/lit						
DRYING	<u>WITH AIR AT 20°C - 60% humidity</u> <table><tr><td>Out of touch</td><td>in the depth</td><td>time to paint over</td></tr><tr><td>30-60 mins</td><td>2-3 hrs</td><td>4-5 hrs</td></tr></table>	Out of touch	in the depth	time to paint over	30-60 mins	2-3 hrs	4-5 hrs
Out of touch	in the depth	time to paint over					
30-60 mins	2-3 hrs	4-5 hrs					
MIN. TEMPERATURE OF APPLICATION	+ 5° C						
PREPARATION OF SURFACE	On new surface, brush thoroughly the surface and apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS. On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.						
APPLICATION	When the surface is prepared, apply a coat of VETUA with plastic or stainless steel trowel, as a first coat. To obtain a better orientation of the micas, use the trowel on flatter surfaces with small rotational movements.						
CLEANING EQUIPMENT AND TOOLS	With water immediately after the use.						
NOTE	Available in packaging of 1L – 4L – 14L.						
STORAGE	The product must be kept in its original intact packaging in an environment which must be protected from freezing and excessive heat and therefore at a temperature not lower than +5 °C and not higher than +35 °C. The information relating to labeling and handling is contained in the relevant safety data sheet. Liquid or solid residues and empty containers must be disposed of according to local regulations. FEAR THE FROST.						

The information, data and suggestions contained in this technical sheet are exact and accurate and must therefore be considered reliable and for informational purposes only and in any case they cannot imply a guarantee on our part, being the conditions of use outside our strict control, therefore they do not release the customer from the burden and responsibility of verifying the suitability of the product for the specific intended use.